

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**SECTION 1: IDENTIFICATION**

Product name : Rubber Care Spray

Product code : 0890 110

**Manufacturer or supplier's details**

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway  
Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National  
Poisons Centre: 131 126

E-mail address : product@wurth.com.au

**Recommended use of the chemical and restrictions on use**

Recommended use : Care product

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Aerosols : Category 1

Skin corrosion/irritation : Category 2

Specific target organ toxicity -  
single exposure : Category 3

Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

## Rubber Care Spray

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

H229 Pressurised container: May burst if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.

Precautionary statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

May displace oxygen and cause rapid suffocation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 30 -< 60
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	>= 10 -< 20
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 10 -< 20
Propane	74-98-6	< 10

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
 Date of first issue: 08.12.2016

Propan-2-ol	67-63-0	< 10
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 1 -< 10
Isobutane	75-28-5	< 10
n-Hexane	110-54-3	< 3

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 If not breathing, give artificial respiration.  
 If breathing is difficult, give oxygen.  
 Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 If vomiting occurs have person lean forward.  
 Call a physician or poison control centre immediately.  
 Rinse mouth thoroughly with water.  
 Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Gas reduces oxygen available for breathing.  
 May be fatal if swallowed and enters airways.  
 Causes skin irritation.  
 May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

## Rubber Care Spray

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 2YE

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and dis-

**Rubber Care Spray**

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

posal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

- |                             |   |  |
|-----------------------------|---|--|
| Technical measures          | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  |
| Local/Total ventilation     | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.  |
| Advice on safe handling     | : | Do not get on skin or clothing.<br>Avoid breathing spray.<br>Do not swallow.<br>Avoid contact with eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep container tightly closed.<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br>Do not spray on an open flame or other ignition source. |
| Hygiene measures            | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.<br>When using do not eat, drink or smoke.<br>Wash contaminated clothing before re-use.   |
| Conditions for safe storage | : | Store locked up.<br>Keep tightly closed.<br>Keep in a cool, well-ventilated place.<br>Store in accordance with the particular national regulations.<br>Do not pierce or burn, even after use.<br>Keep cool. Protect from sunlight.   |
| Materials to avoid          | : | Do not store with the following product types:<br>Self-reactive substances and mixtures<br>Organic peroxides<br>Oxidizing agents<br>Flammable liquids<br>Pyrophoric liquids  |

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
 Date of first issue: 08.12.2016

Pyrophoric solids  
 Self-heating substances and mixtures  
 Explosives

Recommended storage temperature : 5 - 35 °C

Storage period : 24 Months

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	AU OEL
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	TWA	500 ppm 1,760 mg/m <sup>3</sup>	AU OEL
		STEL	1,000 ppm 3,500 mg/m <sup>3</sup>	AU OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	STEL	500 ppm 2,050 mg/m <sup>3</sup>	AU OEL
		TWA	400 ppm 1,640 mg/m <sup>3</sup>	AU OEL
		TWA	900 mg/m <sup>3</sup>	AU OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propan-2-ol	67-63-0	STEL	500 ppm 1,230 mg/m <sup>3</sup>	AU OEL
		TWA	400 ppm 983 mg/m <sup>3</sup>	AU OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	TWA	900 mg/m <sup>3</sup>	AU OEL
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	AU OEL
		TWA	50 ppm	ACGIH

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
------------	---------	--------------------	---------------------	---------------	---------------------------	-------

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
 Date of first issue: 08.12.2016

Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI
n-Hexane	110-54-3	2,5-Hexanedi-one	Urine	End of shift	0.5 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

#### Hand protection

Material : Nitrile rubber  
 Break through time : 480 min  
 Glove thickness : 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Appearance : Aerosol containing a liquefied gas

Propellant : Butane, Propane, Isobutane

Colour : Colorless to pale yellow

Odour : aliphatic

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : < -20 °C  
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 12 %(V)

Lower explosion limit / Lower flammability limit : 0.8 %(V)

Vapour pressure : 2,200 - 3,400 hPa (23 °C)

Relative vapour density : Not applicable

Relative density : 0.66

Density : 0.66 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : partly miscible

Solubility in other solvents : soluble  
Solvent: organic solvents

Partition coefficient: n- : Not applicable



**Rubber Care Spray**

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : 50 °C

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Metal corrosion rate : Not corrosive to metals

Particle characteristics  
Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Components:****Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): 16,750 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 259.354 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,350 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Propan-2-ol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 3,350 mg/kg  
Remarks: Based on data from similar materials

**Isobutane:**

- Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**n-Hexane:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

- Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

- Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Propan-2-ol:**

- Species : Rabbit

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Result : No skin irritation

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.

**n-Hexane:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Propan-2-ol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**n-Hexane:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative  
Remarks : Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Propan-2-ol:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative  
Remarks : Based on data from similar materials

**n-Hexane:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Method: OECD Test Guideline 474  
Result: negative

**Propan-2-ol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**Isobutane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**n-Hexane:**

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

**Propan-2-ol:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 451  
Result : negative

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials



## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

**n-Hexane:**

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Propan-2-ol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**Isobutane:**

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapour)  
Result: positive

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Butane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Assessment : May cause drowsiness or dizziness.

**Propane:**

Assessment : May cause drowsiness or dizziness.

**Propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Isobutane:**

Assessment : May cause drowsiness or dizziness.

**n-Hexane:**

Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Components:****n-Hexane:**

Exposure routes : inhalation (vapour)  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity****Components:****Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species : Rat, male  
NOAEL : 10.504 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rat  
NOAEL : 12.47 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Propan-2-ol:**

Species : Rat  
NOAEL : 12.5 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 104 Weeks

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat, male  
NOAEL : 10.504 mg/l  
LOAEL : 31.652 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

**Isobutane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**n-Hexane:**

Species : Mouse  
LOAEL : 1.76 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3,973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Product:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Components:****n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction

---

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 0.1 - 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

**Propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

## Rubber Care Spray

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

aquatic invertebrates      Exposure time: 24 h

Toxicity to microorganisms      :    EC50 (*Pseudomonas putida*): > 1,050 mg/l  
Exposure time: 16 h

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish      :    LL50 (*Oncorhynchus mykiss* (rainbow trout)): 12 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other      :    EL50 (*Daphnia magna* (Water flea)): 3 mg/l  
aquatic invertebrates      Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic      :    EL50 (*Selenastrum capricornutum* (green algae)): > 10 - 100  
plants      mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (*Selenastrum capricornutum* (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**n-Hexane:**

Toxicity to fish      :    LC50 (*Pimephales promelas* (fathead minnow)): 2.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other      :    EL50 (*Daphnia magna* (Water flea)): 3.88 mg/l  
aquatic invertebrates      Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic      :    EL50 (*Pseudokirchneriella subcapitata* (green algae)): 55 mg/l  
plants      Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (*Pseudokirchneriella subcapitata* (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials



**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Persistence and degradability****Components:****Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Propan-2-ol:**

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)  
COD: 2,23  
BOD/COD: 53 %

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 81 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**n-Hexane:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Butane:**

Partition coefficient: n- : log Pow: 2.31  
octanol/water

**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Partition coefficient: n- : log Pow: 3.6  
octanol/water

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Partition coefficient: n- : log Pow: > 4  
octanol/water      Remarks: Based on data from similar materials

**Propan-2-ol:**

Partition coefficient: n- : log Pow: 0.05  
octanol/water

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: > 3 - < 4  
octanol/water      Remarks: Based on data from similar materials

**Isobutane:**

Partition coefficient: n- : log Pow: 2.8  
octanol/water

**n-Hexane:**

Partition coefficient: n- : log Pow: 4  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Rubber Care Spray**

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)
- 

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

- UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : yes

**IATA-DGR**

- UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

- UN number : UN 1950  
Proper shipping name : AEROSOLS  
(Hydrocarbons, C6, isoalkanes, <5% n-hexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes

**Rubber Care Spray**

Version 6.1      Revision Date: 26.03.2024      SDS Number: 10704707-00015      Date of last issue: 21.11.2023  
Date of first issue: 08.12.2016

---

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Hazchem Code : 2YE  
Environmentally hazardous : yes

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) Instrument : No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 605 g/l

**The components of this product are reported in the following inventories:**

AllC : All ingredients listed or exempt.

---

**SECTION 16: ANY OTHER RELEVANT INFORMATION****Further information**

Revision Date : 26.03.2024

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

---

## Rubber Care Spray

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

**Rubber Care Spray**

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
6.1	26.03.2024	10704707-00015	Date of first issue: 08.12.2016

---

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN